

SELECTION SUMMARY

AUTOMATION

PLC SERIES	VARIANT	SUPPLY	No of SLOTS	DI	DO	FI	FO	ANALOG INPUTS					AO	COMMUNICATION																								
								TC	RTD	NTC / PTC	V	I		RS485 Slave	RS485 Master	Ethernet / USB	RTC																					
MiBRX - Rail	MiBRX-2M	24VDC	2	3 DI*	-	1 CH - 5kHz*	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-															
	MiBRX-4M	4	4 + 1 (V / DI)*	-	1CH - 5kHz	1*NTC																		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	MiBRX-6M	6	8 / 12 DI, 10 + 1 (V / DI)*	4 RO*	1 CH - 5kHz	1NTC																																
MiBRX - Panel	MiBRX-72	24VDC / 230VAC	2	3 + 1 (V / DI)*	3 / 4 RO*	1 CH - 5kHz	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-															
	MiBRX-48		2	5 / 6 (V / DI)*	-	1 CH - 5kHz																		1NTC														
	MiBRX-96		6	3 / 5 + 1 (V / DI)*	-	1 CH - 5kHz																		1NTC														
MiBRX IO Cards	-	-	-	4**	2 RO (10A)	1 CH - 10kHz	1 CH - 200kHz + 2 TO NPN	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-														
				5 (230VAC)	3 RO*																				2**	2 (PT1000)	2 NTC	2**	2**	1 (V / I)								
				6**	4 RO*																				3**	2 RTD + 1**	2 PTC	3**	3**	1 V + 1 I								
				-	5 RO (1.5A)																				2TC + 1**	2RTD + 1**	-	-	-	2 V*								
				-	4 TO*																				-	-	-	-	-	2 I*								
				2DI + 3RO	4 TO*																				Wifi Card (MQTT for IOT)					-								
2DI + 2TO	4 TO*	2DI + 1TC/RTD					-																															
-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-															
FLEXYS	FL-GT35	24VDC / 230VAC	3	4 (PS)*	-	2 CH - 5kHz	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-															
	PANEL TX4		4	4 (PS)*	2 CH - 5kHz	As per Card selection																		RS485-03	YES	-	-	-										
	RAIL		4	4 (PS)*	2 CH - 5kHz *																																	
FLEXYS IO CARDS	-	-	-	10	8 RO	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-															
				14	8 TO																			4 / 5 TC *	4 RTD	3 NTC + 3	16 V	6 I	4 (V / I)									
				4DI + 4RO	-																			4 Universal					-									
				-	-																			4 Loadcell					-									
				-	-																			3 Universal (AI) + 2 Universal (AO)					-									
				-	-																			-	-	-	-	-	-									
UNIX	UNIX-1	230V	-	3 + 1 (V / DI)	2 RO + 2 TO	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-															
TWIX	TWIX-1	24VDC /	-	6	4 RO	1 CH - 5kHz	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-															
	TWIX-2	230VAC		6 + (2V / DI)	5 RO																			1 TC / RTD	-	-	-	RS485-03										
	TWIX-3	24VDC		8	6 TO																			2 TC / RTD	-	2	2	1	RS485-02									
DIGIX	DIGIX-1	24VDC /	-	8	5 RO	1 CH - 5kHz	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-															
	DIGIX-1-B	24VDC		8	5 RO																			1 TC / RTD	-	-	-	RS485-03										
MM303X	MM3030-4	24VDC	-	10	8 TO	1 CH - 12kHz, 2 CH - 7.5kHz	2 CH - 50kHz	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-															
	MM3032-2	24VDC		8	6 RO	1 CH - 5kHz	-	-	-	-	1 NTC	-	-	-	1 (V/I)	-	-	-	-	RS485-03	YES	-	-															
	MM3032-2	230V		8	6 RO	1 CH - 5kHz	-	-	-	-	-	-	2 (V/I)	1 V	-	-	-	-	-	RS485-03	NO	-	-															
Note: MiBRX Series	<p>*Pluggable card variant available</p> <p>** Pluggable + Isolated (ISO) variant available e.g., MiBRX-SC-DI0X-ISO, MiBRX-SC-DI0X-P</p> <ul style="list-style-type: none"> - Digital input can be configured as analog input (0-10V) Use of RO and AO cards are limited in 230VAC variants. - Mixed usages for RO/AO limits are auto-managed in Selpro settings or refer to product manual for detail use of RO and AO cards are limited in 230VAC variants. - A maximum of 25 variables of type VAR_IN_OUT and VAR_OUTPUT (each 32-bit) can be retained when operating at 110V. - Non-Isolated DI cards supports only in Non-ISO variant. - Pluggable variant is not available for MiBRX-SC-RO05. - Refer to the IO card and base module compatibility guidelines to ensure effective and valid IO card combinations. 																																					
	Note: Flexys series	<ul style="list-style-type: none"> - The 230V model supports a maximum of 2 FL-SC-RO08-CE-RoHS or FL-SC-DI04-RO04-CE-RoHS cards only. - The 230V model supports only one of the following analog output cards: FL-SC-AO04-V-CE-RoHS or FL-SC-AO04-I-CE-RoHS - Cannot be used together: FL-SC-AO04-V-CE-RoHS / FL-SC-AO04-I-CE-RoHS with FL-SC-RO08-CE-RoHS or FL-SC-DI04-RO04-CE-RoHS. - Supports combination of: FL-SC-AI03-U-AO02-U with up to 2 FL-SC-RO08-CE-RoHS cards. - Does not support using FL-SC-AI03-U-AO02-U together with FL-SC-AO04-V-CE-RoHS or FL-SC-AO04-I-CE-RoHS. - Maximum 2 units of FL-SC-AI03-U-AO02-U are supported on the 230V model. - A maximum of 25 variables of type VAR_IN_OUT and VAR_OUTPUT (each 32-bit) can be retained when operating at 110V. 																																				

Note: Please refer to product datasheet or operating manuals for technical details, prior product selection.